



PRODUCT DATA SHEET

Iso-Butanol

Produced using technology licensed by The Dow Chemical Company.

CHEMICAL DESCRIPTION:

Name : Isobutanol
CAS number : 78-83-1
Type : Solvent

Isobutanol is a low boiling alcohol and is clear and colorless with a sweet musty odor.

APPLICATIONS:

- Paint & Coating
- Ink
- Textile processing
- I&I cleaning products
- Floatation agent
- Chemical intermediate

TYPICAL PROPERTIES:

Physical Property*	Units	Typical Value
Physical appearance (25°C)	-	Colourless liquid
Normal butanol	wt%, max	0.1
Iso-butanol	wt%, max	99.5-100.0
Acidity	wt%, max	0.003
Water	wt%, max	0.1
Colour	PtCo, max	5
Molecular weight	g/mol	74.12
Viscosity @ 20°C	cP	3.102
Surface tension (1% @ 25°C)	dynes/cm	23
Flash point, PMCC	°C	31
Boiling point @ 760 mmHg	°C	108
Freezing point	°C	-90.0
Relative evaporation rate. nBuAc = 1	-	0.74

*These properties are typical but do not constitute specifications.

FOR MORE INFORMATION

Please contact **PETRONAS Chemicals Group Berhad (PCGB)**

Level 33, Tower 1, PETRONAS Twin Towers, Kuala Lumpur City Centre, 50088, KUALA LUMPUR, MALAYSIA.

Tel: +(603) 20515000 or visit our site <https://www.petronas.com/pcg/>

Sales contact person; Tel: +(603) 2331 6063, Email: jjahaur.chong@petronas.com.my



MS ISO 9001 2000 REG. NO. AR4.088
(DERIVATIVES PLANT)

MS ISO 14001 CERT. NO. 00081001

IMPORTANT NOTICE:

Information contained in this document is accurate and reliable to the best of the knowledge and belief of PETRONAS Chemical Group Berhad. The suggestions and recommendations offered herein serve as a guide in the use of these material and cannot be guaranteed because the conditions of use are beyond PCGB's control. PCGB assumes no responsibility for the use of information supplied, the application, adaption or processing of the products described herein and here by disclaims all liability (except as otherwise provided by the law) in regard to such use.